

Heat shrink tubing



Heat Shrink Tubing are supplied in various shrink ratios, materials and thickness. Available in several colors with a wide range of operating temperatures, most are flame retardant. Lined tubing forms a bond to the underlying surface filling small voids. When cool this creates a barrier against water, moisture, dirt and other contaminants. Custom lengths are available. Call for ordering information.

CPX100 Features

Thin Wall Flexible Polyolefin
Flame Retardant except Clear
Continuous Operating Temperature:
-55° to 135°C (-67° to 275°F)
Shrink Temperature:
120°C (248°F)
Meets UL224, CSA C22.2 No. 198.1
MIL=DTL-23053/5 Class 1&2
AM53636& 3637, DEF STAN 59-97
Issue 3, Type 2a
Other Colors Available:
Red, White, Blue, Yellow,
Green, Clear
Packing:
Spools and 48" sticks

CPA100 Features

Thin Dual Wall Flexible Polyolefin
Flame Retardant except Clear
Continuous Operating Temperature:
-55° to 135°C (-67° to 275°F)
Shrink Temperature:
120°C (248°F)
Meets MIL-DTL-23053/4 Class 3
Other Colors Available:
Red, Blue, Clear
Packing: Spools and 48" sticks

DERAY IHKT Features

Thin Dual Wall Flexible Polyolefin
Flame Retardant
Continuous Operating Temperature:
-55° to 135°C (-67° to 275°F)
Shrink Temperature: 100°C (212°F)
Meets VG95343, Part 12, type D
Other Colors Available:
Red, Blue, Clear
Packing: 48" sticks

CFHR Features

Heavy Wall Crosslinked Polyolefin
Continuous Operating Temperature:
-55° to 135°C (-67° to 275°F)
Shrink Temperature: 120°C (248°F)
Thermoplastic Adhesive Liner for
environmental protection & insulation
Packaging: 6" or 48" sticks

CPX100 Heat Shrink (2:1 Ratio)		CABLE OD	
		Max.	Min.
CPX100-0047-BLK	3/64"	0.047	0.023
CPX100-0063-BLK	1/16"	0.063	0.031
CPX100-0094-BLK	3/32"	0.094	0.047
CPX100-0125-BLK	1/8"	0.125	0.063
CPX100-0187-BLK	3/16"	0.188	0.094
CPX100-0250-BLK	1/4"	0.250	0.125
CPX100-0312-BLK	5/16"	0.313	0.188
CPX100-0375-BLK	3/8"	0.375	0.250
CPX100-0500-BLK	1/2"	0.500	0.313
CPX100-0750-BLK	3/4"	0.750	0.375
CPX100-1000-BLK	1"	1.000	0.500
CPX100-1250-BLK	1 1/4"	1.250	0.625
CPX100-1500-BLK	1 1/2"	1.500	0.750
CPX100-2000-BLK	2"	2.00	1.000
CPX100-3000-BLK	3"	3.00	1.500
CPX100-4000-BLK	4"	4.00	2.000
CPA100 Heat Shrink (3:1 Ratio)			
CPA100-0125-BLK	1/8"	0.125	0.040
CPA100-0187-BLK	3/16"	0.188	0.060
CPA100-0250-BLK	1/4"	0.250	0.080
CPA100-0312-BLK	5/16"	0.313	0.100
CPA100-0375-BLK	3/8"	0.375	0.125
CPA100-0500-BLK	1/2"	0.500	0.160
CPA100-0750-BLK	3/4"	0.750	0.250
CPA100-1000-BLK	1"	1.000	0.320
CPA100-1250-BLK	1 1/4"	1.250	0.416
CPA100-1500-BLK	1.57"	1.570	0.510
Deray IHKT Heat Shrink (4:1 Ratio)			
DERAYIHKT-0157-BLK-4FT5TK		0.157	0.039
DERAYIHKT-0315-BLK-4FT5TK		0.315	0.080
DERAYIHKT-0472-BLK-4FT5TK		0.472	0.118
DERAYIHKT-0630-BLK-4FT5TK		0.630	0.160
DERAYIHKT-0945-BLK-4FT5TK		0.945	0.240
DERAYIHKT-1260-BLK-4FT5TK		1.260	0.315
DERAYIHKT-2047-BLK-4FT5TK		2.047	0.512
CFHR Heat Shrink (6:1 Ratio)			
CFHR-0750-BLK-LINED-4FT5TK		0.75	0.125
CFHR-1300-BLK-LINED-4FT5TK		1.30	0.220
CFHR-1750-BLK-LINED-4FT5TK		1.75	0.290
CFHR-2000-BLK-LINED-4FT5TK		2.00	0.330
CFHR-2750-BLK-LINED-4FT5TK		2.75	0.460
CFHR-3500-BLK-LINED-4FT5TK		3.50	0.673
CFHR-4700-BLK-LINED-4FT5TK		4.70	0.900